

铜芯聚氯乙烯绝缘聚氯乙烯护套屏蔽软电缆

Farrow Cable RVVP

额定电压: Nominal voltage:	300/500V
导体: Conductor:	多股铜导体, 符合GB/T 3956 第5类 (等同于IEC60228.5)
绝缘: Insulation:	聚氯乙烯 (PVC) 混合料
屏蔽: Screen :	镀锡铜丝编织屏蔽, 覆盖率大于85%
护套: Sheath:	柔性聚氯乙烯混合料 (PVC), 灰色 (RAL7001)
绝缘标识: Identification of cores:	≤5芯, 彩色芯线; >5芯, 黑色芯线白色数字编号, 可含黄绿接地线
芯线数: No. of core:	2~24
截面积: Cross section:	0.5~25mm ²
测试电压: Test voltage:	2000V, 5min
绝缘电阻: Insulation resistance:	> 20MΩ x km
使用温度 (固定安装): Operating temp. (static):	-30 ~ +70°C
使用温度 (移动安装): Operating temp. (flexing):	-5 ~ +70°C
弯曲半径: Bending radius:	15x电缆外径
阻燃特性: Flame retardance:	IEC 60 332.1
参考标准: Ref. to:	JB 8734, VDE 0281


应用/Application:

较之RVV电缆, 由于采用了铜丝编织屏蔽, 本产品具有更佳的电磁兼容特性。故特别适用于电磁环境较恶劣, 安装距离较小的安装场所。产品可安装在桥架, 软管中, 用于室内安装。

A good EMC for braid screen, It is good at the High EMC and narrow space. Not for use outside closed rooms. It is same with (NYSLCY cable and H05VC4V-F cable, for installation in closed conduits and tubes in door.

注释/Remark:

- ①更大额定电压450/750V, 600/1000V电缆, 请与我司联系;
- ②更多芯线标识请与我司联系;
- ③其他专用场所使用产品 (耐高低温、耐腐蚀、耐切削等性能) 请与我司联系。



铜芯聚氯乙烯绝缘聚氯乙烯护套屏蔽软电缆

Farrow Cable RVVP

参数表

产品编号 Part Number	规格芯线数×标称截面积 Number of cores & mm ² per conductor	近似外径 Out Diameter mm	耗铜量 Copper Weight kg/km	净重 Weight kg/km
054 0102	2 × 0.50	6.5	24.8	62.0
054 0103	3 G 0.50	6.8	30.6	72.0
054 0104	4 G 0.50	7.6	37.1	88.0
054 0105	5 G 0.50	8.2	43.8	104.0
054 0106	6 G 0.50	9.2	56.0	130.0
054 0107	7 G 0.50	9.2	61.0	135.0
054 0108	8 G 0.50	9.8	69.0	150.0
054 0110	9 G 0.50	11.5	84.0	190.0
054 0112	12 G 0.50	12.0	95.0	215.0
054 0118	18 G 0.50	14.2	140.0	307.0
054 0124	24 G 0.50	17.2	185.0	420.0
054 0202	2 × 0.75	7.0	31.2	74.0
054 0203	3 G 0.75	7.4	39.4	87.0
054 0204	4 G 0.75	8.2	48.4	108.0
054 0205	5 G 0.75	9.2	64.0	137.0
054 0206	6 G 0.75	9.9	74.0	159.0
054 0207	7 G 0.75	9.9	81.0	165.0
054 0208	8 G 0.75	10.5	91.0	189.0
054 0210	9 G 0.75	12.7	111.0	239.0
054 0212	12 G 0.75	13.2	136.0	276.0
054 0218	18 G 0.75	15.6	188.0	390.0
054 0224	24 G 0.75	19.0	251.0	532.0
054 0302	2 × 1.0	7.3	36.8	82.0
054 0303	3 G 1.0	7.9	47.4	101.0
054 0304	4 G 1.0	8.6	59.0	122.0
054 0305	5 G 1.0	9.6	77.0	155.0
054 0306	6 G 1.0	10.4	89.0	181.0
054 0307	7 G 1.0	10.4	99.0	189.0
054 0308	8 G 1.0	11.3	111.0	216.0
054 0310	10 G 1.0	13.6	146.0	289.0
054 0312	12 G 1.0	14.0	167.0	321.0
054 0318	18 G 1.0	16.6	234.0	455.0
054 0324	24 G 1.0	19.9	313.0	612.0
054 0402	2 × 1.5	8.4	48.5	110.0
054 0403	3 G 1.5	9.2	70.0	143.0
054 0404	4 G 1.5	10.0	86.0	172.0
054 0405	5 G 1.5	11.0	104.0	210.0
054 0406	6 G 1.5	12.1	121.0	250.0
054 0407	7 G 1.5	12.1	135.0	262.0
054 0408	8 G 1.5	12.8	161.0	309.0
054 0410	10 G 1.5	15.8	199.0	396.0
054 0412	12 G 1.5	16.3	228.0	443.0

产品编号 Part Number	规格芯线数×标称截面积 Number of cores & mm ² per conductor	近似外径 Out Diameter mm	耗铜量 Copper Weight kg/km	净重 Weight kg/km
054 0418	18 G 1.5	19.2	323.0	629.0
054 0424	24 G 1.5	23.4	446.0	868.0
054 0502	2 × 2.5	10.1	78.0	164.0
054 0503	3 G 2.5	10.9	103.0	204.0
054 0504	4 G 2.5	12.1	130.0	255.0
054 0505	5 G 2.5	13.4	166.0	319.0
054 0506	6 G 2.5	14.7	194.0	380.0
054 0507	7 G 2.5	14.7	217.0	400.0
054 0508	8 G 2.5	15.0	245.0	455.0
054 0510	10 G 2.5	19.0	304.0	582.0
054 0512	12 G 2.5	19.6	352.0	655.0
054 0518	18 G 2.5	23.4	515.0	957.0
054 0524	24 G 2.5	28.2	697.0	1,298.0
054 0603	3 G 4.0	12.2	150.0	273.0
054 0604	4 G 4.0	13.6	200.0	352.0
054 0605	5 G 4.0	15.0	243.0	428.0
054 0607	7 G 4.0	16.5	322.0	541.0
054 0703	3 G 6.0	14.8	226.0	399.0
054 0704	4 G 6.0	16.4	289.0	500.0
054 0705	5 G 6.0	18.1	352.0	610.0
054 0706	7 G 6.0	19.9	471.0	774.0
054 0803	3 G 10.0	18.7	374.0	647.0
054 0804	4 G 10.0	20.9	481.0	824.0
054 0805	5 G 10.0	23.2	601.0	1,019.0
054 0903	3 G 16.0	21.4	568.0	918.0
054 0904	4 G 16.0	23.8	736.0	1,171.0
054 0905	5 G 16.0	26.3	905.0	1,434.0
054 1004	4 G 25.0	30.0	1,125.0	1,797.0
054 1005	5 G 25.0	33.3	1,388.0	2,217.0

注释/Remark:

- 1/ 额定电压为450/750V及600/1000V的线的型号为RVVP 450/750V及VVVP 600/1000V;
- 2/ X-不含黄绿接地保护芯线, G-含黄绿接地保护芯线;
- 3/ 标准包装100m、500m、1000m;
- 4/ 更多规格请与我司联系。